



### TECHNICAL DATA

Body Type	Line mount
Capacity	95 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	3

**OPTION SELECTION EXAMPLE: YRDCLANAJ**

CONTROL		(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)	
<b>L</b>	Standard Screw Adjustment	<b>A</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b>	Buna-N
<b>C</b>	Tamper Resistant - Factory Set	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b>	Viton
<b>F</b>	Hex Head Screw with Locknut	<b>C</b>	150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
<b>W</b>	Hex Wrench Adjustment	<b>D</b>	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
<b>Y</b>	manilla de tres agarres	<b>E</b>	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
		<b>N</b>	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		
		<b>Q</b>	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
		<b>W</b>	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

**PRIMARY CARTRIDGE**
**(A)**

<b>A</b>	A (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula )
<b>A</b>	A (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral )

**INCLUDED COMPONENTS**

Part	Description	Quantity
210-010*	Spool	1
230-032*	Sleeve	1
250-022*	Retainer	2
295-002*	Handle	1
300-001-005*	Screw	2
300-002-005*	Screw	1
402-003-075*	Snap Ring	2
500-001-016*	O-Ring	2
515-002-515*	Backup Ring	2
600-052*	Spring	2
800-001-080*	Ball	4
812-001-001*	Pin	1
840-001*	Handle	1
RPECLAN	Cartridge - Primary	3