



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Capacity	95 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	3

OPTION SELECTION EXAMPLE: YRDCLANAJ

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
		V Viton	

PRIMARY CARTRIDGE	(A)
A A (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula.)	

INCLUDED COMPONENTS

Part	Description	Quantity
210-010*	Spool	1
230-032*	Sleeve	1
250-022*	Retainer	2
295-002*	Handle	1
300-001-005*	Screw	2
300-002-005*	Screw	1
402-003-075*	Snap Ring	2
500-001-016*	O-Ring	2
515-002-515*	Backup Ring	2
600-052*	Spring	2
800-001-080*	Ball	4
812-001-001*	Pin	1
840-001*	Handle	1
RPECLAN	Cartridge - Primary	3