



### TECHNICAL DATA

Capacity	240 L/min.
----------	------------

**OPTION SELECTION EXAMPLE: YRFLLANCN**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	
	<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
	<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

**PRIMARY CARTRIDGE (C)**

<b>C</b> 30 psi (2 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>A</b> 4 psi (0,3 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>B</b> 15 psi (1 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>D</b> 50 psi (3,5 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>E</b> 75 psi (5 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>F</b> 100 psi (7 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>Z</b> 1 psi (0,07 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXHAXCN	Cartridge	1
RVGALAN	Cartridge - Primary	1