



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Capacity	240 L/min.
----------	------------

**OPTION SELECTION EXAMPLE: YRFLLANCN**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
		<b>V</b> Viton	

**PRIMARY CARTRIDGE (C)**

<b>C</b>	30 psi (2 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>A</b>	4 psi (0,3 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>B</b>	15 psi (1 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>D</b>	50 psi (3,5 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>E</b>	75 psi (5 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>F</b>	100 psi (7 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )
<b>Z</b>	1 psi (0,07 bar) (with RVGA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXHAXCN	Cartridge	1
RVGALAN	Cartridge - Primary	1