



**CONFIGURATION OPTIONS**

**Model Code Example: YRFMLANCJ**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set	<b>W</b> 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	

**PRIMARY CARTRIDGE**

(C)

<b>C</b>	30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>A</b>	4 psi (0,3 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>B</b>	15 psi (1 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>D</b>	50 psi (3,5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>E</b>	75 psi (5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>F</b>	100 psi (7 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>Z</b>	1 psi (0,07 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>Z</b>	1 psi (0,07 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>F</b>	100 psi (7 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>E</b>	75 psi (5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>D</b>	50 psi (3,5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>C</b>	30 psi (2 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>B</b>	15 psi (1 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>A</b>	4 psi (0,3 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXFAXCN	Cartridge	2
RDFALAN	Cartridge - Primary	2