



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	200 L/min.
	8.6 mm
	Through
	2

OPTION SELECTION EXAMPLE: YRFMLANCJ

(L) (A) (N)

L	A	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)	N
C	W	800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)	V

PRIMARY CARTRIDGE (C)

C	30 psi (2 bar) (with RDFA primary cartridge,)
A	4 psi (0,3 bar) (with RDFA primary cartridge,)
B	15 psi (1 bar) (with RDFA primary cartridge,)
D	50 psi (3,5 bar) (with RDFA primary cartridge,)
E	75 psi (5 bar) (with RDFA primary cartridge,)
F	100 psi (7 bar) (with RDFA primary cartridge,)
Z	1 psi (0,07 bar) (with RDFA primary cartridge,)
Z	1 psi (0,07 bar) (with RDFA3 primary cartridge,)
F	100 psi (7 bar) (with RDFA3 primary cartridge,)
E	75 psi (5 bar) (with RDFA3 primary cartridge,)
D	50 psi (3,5 bar) (with RDFA3 primary cartridge,)
C	30 psi (2 bar) (with RDFA3 primary cartridge,)
B	15 psi (1 bar) (with RDFA3 primary cartridge,)
A	4 psi (0,3 bar) (with RDFA3 primary cartridge,)

INCLUDED COMPONENTS

Part	Description	Quantity
CXFAXCN	Cartridge	2
RDFALAN	Cartridge - Primary	2