



TECHNICAL DATA

NOTE:

	200 L/min.	DATA
	8.6 mm	MAY
	Through	VARY
	2	BY

CONFIGURATION

L	
A	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)
N	
C	Range Letter(s) of Subordinate Cartridge 30 psi (2 bar) (with RDFA primary cartridge,)
K	Port and Material Designation All Ports — SAE 10; Aluminum

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: YRFMLANCK

(L)	(A)	(N)
L	<p>A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)</p> <p>B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar)</p> <p>C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar)</p> <p>D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar)</p> <p>E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar)</p> <p>S 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar)</p> <p>W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)</p>	N V

PRIMARY CARTRIDGE

(C)

C	30 psi (2 bar) (with RDFA primary cartridge,)
A	4 psi (0,3 bar) (with RDFA primary cartridge,)
B	15 psi (1 bar) (with RDFA primary cartridge,)
D	50 psi (3,5 bar) (with RDFA primary cartridge,)
E	75 psi (5 bar) (with RDFA primary cartridge,)
F	100 psi (7 bar) (with RDFA primary cartridge,)
Z	1 psi (0,07 bar) (with RDFA primary cartridge,)
Z	1 psi (0,07 bar) (with RDFA3 primary cartridge,)
F	100 psi (7 bar) (with RDFA3 primary cartridge,)
E	75 psi (5 bar) (with RDFA3 primary cartridge,)
D	50 psi (3,5 bar) (with RDFA3 primary cartridge,)
C	30 psi (2 bar) (with RDFA3 primary cartridge,)
B	15 psi (1 bar) (with RDFA3 primary cartridge,)
A	4 psi (0,3 bar) (with RDFA3 primary cartridge,)

INCLUDED COMPONENTS

Part	Description	Quantity
CXFAXCN	Cartridge	2
RDFALAN	Cartridge - Primary	2