



This assembly provides 2 functions. It provides cross-port relief protection between ports M1 and M2. It also provides anti-cavitation protection for ports M1 and M2.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	Motor mount
Interface	Staffa B150/B200

- NOTES:**
- **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
 - For detailed information regarding the cartridges contained in this assembly, click on the models codes shown in the Included Components tab.

CONFIGURATION OPTIONS

Model Code Example: YRFNLANAM

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L	Standard Screw Adjustment	A	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N
C	Tamper Resistant - Factory Set	W	800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting	V	Viton

PRIMARY CARTRIDGE

(A)

A	A (with RDFA primary cartridge, Direct-acting relief valve)
A	A (with RDFA3 primary cartridge, Non-adjustable direct-acting relief valve)

INCLUDED COMPONENTS

Part	Description	Quantity
CXFBXAN	Cartridge	2
RDFALAN	Cartridge - Primary	2