



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|----------------------|
| | |
| | Eaton/Char-Lynn 2000 |

CONFIGURATION OPTIONS

Model Code Example: YRGULANAL

| (L) | (A) | (N) |
|----------|---|----------------------|
| L | A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) S 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) | N V |

PRIMARY CARTRIDGE

(A)

| | |
|----------|------------------------------------|
| A | A (with RDDA primary cartridge,) |
| A | A (with RDDA3 primary cartridge,) |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|--------------|---------------------|----------|
| 500-001-117* | O-Ring | 2 |
| DSCHXHN | Cartridge | 1 |
| RDDALAN | Cartridge - Primary | 2 |
| RPECLNN | Cartridge | 1 |