



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

---

**CONFIGURATION OPTIONS**

**Model Code Example: YSELLANCK**

	(L)	(A)	(N)
<b>L</b>		<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>N</b>
J			V
O		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
W			

**PRIMARY CARTRIDGE**

(C)

<b>C</b>	30 psi (2 bar) (with RSFC primary cartridge, , )
A	4 psi (0,3 bar) (with RSFC primary cartridge, , )
B	15 psi (1 bar) (with RSFC primary cartridge, , )
D	50 psi (3,5 bar) (with RSFC primary cartridge, , )
E	75 psi (5 bar) (with RSFC primary cartridge, , )
F	100 psi (7 bar) (with RSFC primary cartridge, , )
Z	1 psi (0,07 bar) (with RSFC primary cartridge, , )
Z	1 psi (0,07 bar) (with RSFC8 primary cartridge, , T-8A )
F	100 psi (7 bar) (with RSFC8 primary cartridge, , T-8A )
E	75 psi (5 bar) (with RSFC8 primary cartridge, , T-8A )
D	50 psi (3,5 bar) (with RSFC8 primary cartridge, , T-8A )
C	30 psi (2 bar) (with RSFC8 primary cartridge, , T-8A )
B	15 psi (1 bar) (with RSFC8 primary cartridge, , T-8A )
A	4 psi (0,3 bar) (with RSFC8 primary cartridge, , T-8A )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXFAXCN	Cartridge	1
RSFCLAN	Cartridge - Primary	1