



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	120 L/min.
	10,7 mm
	Through
	2

**OPTION SELECTION EXAMPLE: YSEPLANCJ**

(L) (A) (N)

<b>L</b>	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>N</b> V
----------	--	---------------

**PRIMARY CARTRIDGE**

(C)

<b>C</b>	30 psi (2 bar) (with RSFC primary cartridge, , )
<b>A</b>	4 psi (0,3 bar) (with RSFC primary cartridge, , )
<b>B</b>	15 psi (1 bar) (with RSFC primary cartridge, , )
<b>D</b>	50 psi (3,5 bar) (with RSFC primary cartridge, , )
<b>E</b>	75 psi (5 bar) (with RSFC primary cartridge, , )
<b>F</b>	100 psi (7 bar) (with RSFC primary cartridge, , )
<b>Z</b>	1 psi (0,07 bar) (with RSFC primary cartridge, , )
<b>Z</b>	1 psi (0,07 bar) (with RSFC8 primary cartridge, , T-8A )
<b>F</b>	100 psi (7 bar) (with RSFC8 primary cartridge, , T-8A )
<b>E</b>	75 psi (5 bar) (with RSFC8 primary cartridge, , T-8A )
<b>D</b>	50 psi (3,5 bar) (with RSFC8 primary cartridge, , T-8A )
<b>C</b>	30 psi (2 bar) (with RSFC8 primary cartridge, , T-8A )
<b>B</b>	15 psi (1 bar) (with RSFC8 primary cartridge, , T-8A )
<b>A</b>	4 psi (0,3 bar) (with RSFC8 primary cartridge, , T-8A )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXFAXCN	Cartridge	1
RSFCLAN	Cartridge - Primary	1