



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|------------------------|------------------|
| Body Type | montaje en línea |
| Mounting Hole Diameter | 10,7 mm |
| Mounting Hole Depth | Through |
| Mounting Hole Quantity | 2 |

CONFIGURATION OPTIONS

Model Code Example: YSHCLANAN

| CONTROL | (L) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) |
|---------|--------------------------------|------------------|---|---------------|--------|
| L | Standard Screw Adjustment | A | 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting | N | Buna-N |
| C | Tamper Resistant - Factory Set | B | 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting | V | Viton |
| K | manilla | D | 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting | | |
| | | E | 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | |
| | | W | 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting | | |

PRIMARY CARTRIDGE

(A)

| | |
|---|---|
| A | 4 psi (0,3 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| B | 15 psi (1 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| C | 30 psi (2 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| D | 50 psi (3,5 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| E | 75 psi (5 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| F | 100 psi (7 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| Z | 1 psi (0,07 bar) (with RSHC primary cartridge, Pilot-operated, pistón balanceado secuencia válvula) |
| Z | 1 psi (0,07 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| F | 100 psi (7 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| E | 75 psi (5 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| D | 50 psi (3,5 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| C | 30 psi (2 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| B | 15 psi (1 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |
| A | 4 psi (0,3 bar) (with RSHC8 primary cartridge, Pilot-operated, pistón balanceado secuencia módulo principal con cavidad de control T-8A integral) |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|---------|---------------------|----------|
| CXHAXAN | Cartridge | 2 |
| RSHCLAN | Cartridge - Primary | 2 |