



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	10,7 mm
	Through
	2

CONFIGURATION OPTIONS

Model Code Example: YSHCLANAN

(L)

(A)

(N)

L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N
----------	--	----------

PRIMARY CARTRIDGE

(A)

A	4 psi (0,3 bar) (with RSHC primary cartridge, ,)
B	15 psi (1 bar) (with RSHC primary cartridge, ,)
C	30 psi (2 bar) (with RSHC primary cartridge, ,)
D	50 psi (3,5 bar) (with RSHC primary cartridge, ,)
E	75 psi (5 bar) (with RSHC primary cartridge, ,)
F	100 psi (7 bar) (with RSHC primary cartridge, ,)
Z	1 psi (0,07 bar) (with RSHC primary cartridge, ,)
Z	1 psi (0,07 bar) (with RSHC8 primary cartridge, , T-8A)
F	100 psi (7 bar) (with RSHC8 primary cartridge, , T-8A)
E	75 psi (5 bar) (with RSHC8 primary cartridge, , T-8A)
D	50 psi (3,5 bar) (with RSHC8 primary cartridge, , T-8A)
C	30 psi (2 bar) (with RSHC8 primary cartridge, , T-8A)
B	15 psi (1 bar) (with RSHC8 primary cartridge, , T-8A)
A	4 psi (0,3 bar) (with RSHC8 primary cartridge, , T-8A)

INCLUDED COMPONENTS

Part	Description	Quantity
CXHAXAN	Cartridge	2
RSHCLAN	Cartridge - Primary	2