



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                        |                  |
|------------------------|------------------|
| Body Type              | montaje en línea |
| Mounting Hole Diameter | 7,1 mm           |
| Mounting Hole Depth    | Through          |
| Mounting Hole Quantity | 2                |

**CONFIGURATION OPTIONS**

**Model Code Example: YVELLANCK**

| CONTROL | (L)                            | ADJUSTMENT RANGE | (A)   | SEAL MATERIAL | (N)    |
|---------|--------------------------------|------------------|---|---------------|--------|
| L       | Standard Screw Adjustment      | A                | 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting    | N             | Buna-N |
| C       | Tamper Resistant - Factory Set | B                | 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting   | V             | Viton  |
| K       | manilla                        | D                | 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting      |               |        |
|         |                                | E                | 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting      |               |        |
|         |                                | J                | 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting   |               |        |
|         |                                | K                | 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting     |               |        |
|         |                                | S                | 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting       |               |        |
|         |                                | W                | 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting |               |        |

**PRIMARY CARTRIDGE**

(C)

|   |  |
|---|--|
| C | 30 psi (2 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )   |
| A | 4 psi (0,3 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )  |
| B | 15 psi (1 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )   |
| D | 50 psi (3,5 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula ) |
| E | 75 psi (5 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )   |
| F | 100 psi (7 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula )  |
| Z | 1 psi (0,07 bar) (with RVEA primary cartridge, De venteo, pilot-operated, pistón balanceado alivio válvula ) |

**INCLUDED COMPONENTS**

| Part    | Description         | Quantity |
|---------|---------------------|----------|
| CXFAXCN | Cartridge           | 1        |
| RVEALAN | Cartridge - Primary | 1        |