



CONFIGURATION

Modifier

- NOTES:**
- This manifold contains provisions for both threaded and thru-hole mounting, quantity two of each. See Technical Data table above for sizes.
 - **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

MODIFIER

(/Y3)

/Y3	65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer
	6061-T651 Aluminum, Buna-N
/11	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/10	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/V	6061-T651 Aluminum, Viton
/16	6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/15	6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/S	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
/S4	65-45-12 Ductile Iron, Buna-N, Chem. Black
/S3	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
/Y	65-45-12 Ductile Iron, Viton, Dewatering Oil
/Y4	65-45-12 Ductile Iron, Viton, Chem. Black

PORT DESIGNATORS

Modifiers	Ports
Z2W, /10, /11, /15, /16, /S, /S3, /S4, /V, /Y, /Y3, /Y4	Ports IN & EF: SAE 10; Port CF: SAE 8;

MATERIAL DESIGNATOR

No modifier - inch, aluminum /S MATERIAL DESIGNATOR - Inch, Ductile Iron /M - Metric, Aluminum /T -

Metric, Ductile Iron