



## CONFIGURATION

### NOTES:

Modifier

- Stack height value in technical data table includes seal retainer plate.
- This manifold requires kit 990-120-012 (Buna-N seals) or 990-120-011 (Viton seals) (must be ordered separately).
- Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

### MODIFIER

(/Y3)

<b>/Y3</b>	65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer
	6061-T651 Aluminum, Buna-N
<b>/11</b>	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>/10</b>	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>/V</b>	6061-T651 Aluminum, Viton
<b>/16</b>	6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>/15</b>	6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>/S</b>	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
<b>/S4</b>	65-45-12 Ductile Iron, Buna-N, Chem. Black
<b>/S3</b>	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
<b>/Y</b>	65-45-12 Ductile Iron, Viton, Dewatering Oil
<b>/Y4</b>	65-45-12 Ductile Iron, Viton, Chem. Black